



104

ROOF & CONCRETE PRIMER

PRODUCT DESCRIPTIONS:

DEWITT'S ROOF & CONCRETE PRIMER is a thin penetrating solution of refined oxidized asphalt and petroleum solvents. DEWITT'S ROOF & CONCRETE PRIMER preserves, resaturates, and prolongs the life of dried-out roofing felts.



USES:

DEWITT'S ROOF & CONCRETE PRIMER is used as a general priming coat on concrete decks, metal roofing, gypsum cinder blocks, floors, walls, and asphalt roofs. An excellent primer prior to the use of hot asphalts, fibered asphalt coatings, asphalt emulsions, reflective coatings or asphalt adhesives. Do not use on COAL TAR, EPDM, PVC, TPO roofing systems.

APPLICATION:

Apply DEWITT'S ROOF & CONCRETE PRIMER to dry and dirt free surfaces with brush, roller or spray at a rate of one gallon per 100 sq. ft.. Application rate will depend on condition and porosity of surface to be primed.

SPECIFICATIONS:

Meets Federal Specification SS-A-701B and ASTM D-41

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx) 8lbs

Clean up
Application temperature

Mineral Spirits or DEWITT'S REMOVE-IT
20 °F- 90 °F

COVERAGE:

1 gallon covers approximately 100sq.ft.

PACKAGING:

55 gal drum & 5 gal pail

CAUTION:

Combustible: Keep away from heat and open flame.
Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.