



155

PRO RESATURANT

PRODUCT DESCRIPTIONS:

DEWITT'S PRO RESATURANT is a special blend of selected asphalts, hi-tech fibers, and a mixture of various kinds of penetrating oils. These oils soak down into the existing roof mat to help rejuvenate the old asphalt to the original condition. A thin layer of asphalt remains on the surface to protect it from ultra-violet rays of the sun as well as serve as a binder for the replacement of the gravel or slag.



USES:

APPLICATION:

Remove all loose gravel, dirt and dust from the roof by sweeping or power broom. If gravel is to be used, it must be free of silt. Repair all blisters, breaks or holes in the roof with DEWITT'S PRO FLASH FLASHING CEMENT (#251) and cotton or glass fabric.

BRUSH – Pour directly from the container and spread with a thick fiber roof brush at the rate of 5-8 gallons per 100 sq. ft..

SPRAY – Apply on large areas with the standard mastic pump type equipment that is placed in the material drum. The coating should be sprayed on in one coat at the rate of 5-8 gallons per 100 sq. ft. applied with a 50% overlap of the spray pattern so as to obtain a uniform and continuous film.

After application, gravel should be reapplied at the rate of 400lbs per 100 sq. ft.

SPECIFICATIONS:

PHYSICAL CHARACTERISTICS:

COVERAGE:

PACKAGING:

55 gallon drum, & 5 gallon pail.

CAUTION: