



501

DS 6000 PLUS

DRIVEWAY SEALER (PETROLEUM BASE)

PRODUCT DESCRIPTIONS:

DEWITT'S DS 6000 PLUS DRIVEWAY SEALER is a superior asphalt driveway sealer. When applied it actually welds to the old asphalt driveway giving it a superior bond and many years of service. Renews, waterproofs, and seals asphalt driveways so water cannot get in and freeze. DEWITT'S DS 6000 PLUS DRIVEWAY SEALER is ready to use straight from the container, no mixing or stirring required. DEWITT'S DS 6000 PLUS DRIVEWAY SEALER gives a rich black finish with only one coat.



USES:

DEWITT'S DS 6000 PLUS DRIVEWAY SEALER may be used with complete confidence on any asphalt pavement. DEWITT'S DS 6000 PLUS DRIVEWAY SEALER is a continuing maintenance requirement for parking lots, driveways, gasoline stations, school yards, airport runways, or anywhere that the asphalt surface is exposed to gas and oil spillage, extensive abrasion, or weathering extremes.

APPLICATION:

DEWITT'S DS 6000 PLUS DRIVEWAY SEALER can be applied using a brush, squeegee, roller, or mechanical equipment. Do not apply on rainy, foggy, or extremely humid days or when temperatures are expected to drop below 15°F during the next 24 hours. For best results, apply in the A.M. Allow at least 6 months for new asphalt to cure before using DEWITT'S DS 6000 PLUS DRIVEWAY SEALER. Do not use on concrete surfaces.

PHYSICAL CHARACTERISTICS:

Weight per gallon (approx)	10 lbs
Color	Black
Drying time	At least 24 hours
Clean up	Mineral Spirits, DEWITT'S REMOVE-IT
Application temperature	Above 15°F

COVERAGE:

One gallon covers approximately 100-125 sq. ft.

PACKAGING:

55 gal. drum, 5gal, Bulk

CAUTION:

Combustible: Keep away from heat and open flame.
Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.