



611

99 WET-STICK CAULK

PRODUCT DESCRIPTIONS:

DEWITT'S # 99 WET-STICK CAULK is an all purpose patching cement manufactured with specially blended asphalts, refined oils, mineral stabilizers and reinforced with hi-tech asbestos-free fibers. DEWITT'S # 99 WET-STICK CAULK sets up to form a tough, continuous, moisture-proof film that will retain its pliability for a long period of time. This enables it to expand and to conform to movement of other materials. DEWITT'S # 99 WET-STICK CAULK can be used on wet or dry surfaces



USES:

DEWITT'S # 99 WET-STICK CAULK is an excellent all purpose cement for repairs of all flashings and sealing in roofs. DEWITT'S # 99 WET-STICK CAULK can also be used on brick siding, gutters, glass, marble, stone, cement, metal roofs, stone coping, etc.. Do not use on COAL TAR, EPDM, PVC, or TPO roofing systems.

APPLICATION:

DEWITT'S # 99 WET-STICK CAULK is used directly from the tube. Surface must be free of dirt, dust, and debris. Apply with a caulking gun to surface. Application on wet surface requires cement to be worked into surface for best results.

SPECIFICATIONS:

Meets ASTM 4586-86 and Federal Specification SS-C-153C ASTM D-2822 Type I, except this material is asbestos free.

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	9 lbs.
Flash point (ASTM 093-52)	100° F Min
Drying time	2-3 days, depending on weather conditions
Viscosity at 80° F	Medium to heavy trowel
Service temperature, extended exposure	-40° to 180° F
Resistance to oils and solvents	Poor
Resistance to sunlight	Excellent
Resistance to chemicals	Excellent
Effects of weathering	Minimal
Water Resistance	
Under draining conditions	Excellent
Under continuous submersion	Fair
Restrictions	Do not use on tar roofs
Clean up	Mineral Spirits or DEWITT'S REMOVE-IT
Application temperature	25°-100° F

*For easy application in winter, warm tube to room temperature before application.

COVERAGE:

One gallon covers approximately 7 sq. ft. at 1/4" thick.

PACKAGING:

10.3oz, & 29oz cartridges

CAUTION:

Combustible: Keep away from heat and open flame.
Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.