

313 COOL-TOP WHITE Patching Cement Material Safety Data Sheet

NDA means No Data Available

Identity (As Used on Label and List) No. 313 COOL-TOP WHITE Patching Cement	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.		
Section I	*		
Manufacturer's Name Address (Number, Street, City, State, and Zip Code)	Telephone Number fo	or Informatio	n
DeWitt Products Company	800-962-8599		
	Telephone Number fo		n
5860 Plumer Ave.	313-554-0575		
	Date Prepared		
Detroit, Michigan 48209	January 2012) -	
Section II - Hazardous Ingredients/Identity Info	ormation		
Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS#	OSHA PEL	ACGIH %Wt.
No reportable quantities of hazardous ingredients	are present.		
Degree Of Hazard:Health1FlammabScale:4 = Extreme3 = High2 = Moderate1 = SligSection III - Physical/Chemical Characteristics	ht 0 = Insignificant	0	Special Hazard 0
Boiling Point	Specific Gravity (H ₂ O = 1)		
NDA	1.35		
Vapor Pressure (mm Hg.)	Melting Point		
NDA	NDA		
Vapor Density (AIR = 1)	Evaporation Rate (Ether = 1)		
>1	<1		
Solubility in Water			
Complete			
Appearance and Odor			
White liquid emulsion with slight ammonia odor.			
Write ilquid cirialcien with diight ammonia cach.			
Section IV - Fire and Explosion Hazard Data	Flammable Limits	LEL	UEL
Section IV - Fire and Explosion Hazard Data Flash Point (Method Used) NDA	Flammable Limits	LEL NDA	UEL NDA
Section IV - Fire and Explosion Hazard Data Flash Point (Method Used)	Flammable Limits		-

Special Fire Fighting Procedures

Water may be used to cool closed containers, to prevent pressure build up.

Unusual Fire and Explosion Hazards

The material will not support combustion unless the water has evaporated.

Keep lid on container when not in use.

Section V - Reactivity Data

Stability Unstable Conditions to Avoid

Stable X None known

Incompatibility (Materials to Avoid)

Avoid contact with strong oxidizers.

Hazardous Decomposition

Normal combustion products including CO₂, CO, and various hydrocarbon fragments.

HazardousMay OccurConditions to AvoidPolymerizationMay Not OccurXNone known

Section VI - Health Hazard Data

Route(s) of Entry Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic)

There is no data available addressing medical conditions which are generally recognized as being aggravated by exposure to this product.

Carcinogenic: NTP? IARC Monographs? OSHA Regulated?

No NDA NDA Yes

Signs and Symptoms of Exposure

Eyes: Irritation Skin: Irritation Inhalation: Irritation of throat and lungs. Ingestion: Nausea, vomiting

Medical Conditions Aggravated by Exposure

Vapor may aggravate tissue in nasal and respiratory passages.

Emergency and First Aid Procedures

Eyes: Flush with large amounts of water. **Skin:** Wash area with soap and water.

Inhalation: Remove to fresh air. **Ingestion:** Give 2 glasses of water to dilute. Do not induce

vomiting.

Seek medical help on all above problems.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Contain spill with inert absorbent material.

Waste Disposal Method

Waste should be disposed of according to federal, state, and local regulations.

Precautions to be Taken in Handling and Storing

Do not store above 120°F. Keep from freezing.

Other Precautions

Keep container closed tight and upright to prevent leakage. Keep out of the reach of children.

Section VIII - Control Measures

Respiratory Protection (Specify Type)

If spray mists are generated, wear NIOSH approved particulate respirator.

Ventilation Local Exhaust Normal good ventilation. Special NDA

Mechanical (General) NDA Other NDA

Protective Gloves Eye Protection

Use chemical resistant gloves, if needed, to avoid prolonged or repeated skin contact.

Use splash goggles or face shield when eye contact may occur.

Other Protective Clothing or Equipment

Use chemical resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

Work/Hygienic Practices

Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; launder or dry clean before reuse. Remove contaminated shoes and thoroughly clean and dry before reuse. Cleanse skin thoroughly after contact, before breaks and meals, and at end of work period. Product is removed from skin by waterless hard cleaners followed by washing thoroughly with soap and water.