




502

# DS2000 PLUS

## PRODUCT DESCRIPTION:

DEWITT'S DS2000 PLUS DRIVEWAY SEALER is a high solids, ready to use asphalt emulsion sealer manufactured by colloidal mill process and fortified with rubber for great adhesion and longer wear. DEWITT'S DS2000 PLUS DRIVEWAY SEALER shields asphalt surfaces from elements of the weather and protects against damages caused by chemicals, de-icing salts, and gas and oil products.



## USES:

DEWITT'S DS2000 PLUS DRIVEWAY SEALER may be used with complete confidence on any asphalt pavement. DEWITT'S DS2000 PLUS DRIVEWAY SEALER is a continuing maintenance requirement for parking lots, driveways, gasoline stations, school yards, airport runways, or anywhere that the asphalt surface is exposed to gas and oil spillage, extensive abrasion, or weathering extremes.

## APPLICATION:

DEWITT'S DS2000 PLUS DRIVEWAY SEALER can be applied using a brush, squeegee, roller or mechanical equipment. Do not apply on rainy, foggy, extremely humid days or when temperature is expected to drop below 40°F during the next 24 hours. For best results, apply in the AM. Allow at least three months for new asphalt to cure before using DEWITT'S DS2000 PLUS DRIVEWAY SEALER. Do not use on concrete surfaces.

## SPECIFICATIONS:

Meets Federal Specifications RP-355-D

## PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	10 lbs.
Color	Black
Drying time	12 hours walk-on 24 hours to drive-on at 70% humidity
Clean up	Mineral Spirits or DEWITT'S Remove-It
Application temperature	40°F and rising

**COVERAGE:**

One gallon covers 100-125 sq. ft.

**PACKAGING:**

55 gallon drum, 5 gallon pail

**CAUTION:**

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.