



504

DS1000 PLUS

CRACK FILLER (Asphalt Base)

PRODUCT DESCRIPTION:

DEWITT'S DS1000 PLUS CRACK FILLER is a special blend of liquid asphalt, rubber, plasticizers and fillers for do-it-yourself repair of cracks and expansion joints in concrete, asphalt driveways, and parking areas. DEWITT'S DS1000 PLUS CRACK FILLER forms a tough, elastic sealer strip.



USES:

DEWITT'S DS1000 PLUS CRACK FILLER can be used to fill cracks 3/8" wide or less. DEWITT'S DS1000 PLUS CRACK FILLER can be used on cracks in concrete, asphalt driveways, and parking areas.

APPLICATION:

Place spout tip above crack. Squeeze out DEWITT'S DS1000 PLUS CRACK FILLER while drawing spout along crack. Keep material in crack level with surface. For best results, apply on dry surface when temperature is not expected to drop below 40°F during the next 24 hours. DO NOT APPLY if rain is expected.

SPECIFICATIONS:

Meets ASTM D-244 ands ASTM M-140-70

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	9 lbs.
Color	Black
Drying time	24-48 hours
Clean up	Mineral Spirits or DEWITT'S Remove-It
Application temperature	Above 40°F

COVERAGE:

150 linear feet at 1/4" and 1/4" deep per gallon

PACKAGING:

55 gallon drum, 5 gallon & 1gallon

CAUTION:

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.