



511

DS5000 SUPREME

E-Z STIR RUBBERIZED FILLER/SEALER

PRODUCT DESCRIPTION:

DEWITT'S DS5000 SUPREME SEALER with sand is an E-Z STIR formulated, heavy duty asphalt emulsion driveway sealer manufactured by colloidal mill process and fortified with rubber for added pavement adhesion, and non-discoloring graded aggregate for increased traction and longer life. DEWITT'S DS5000 SUPREME SEALER will also fill small voids in asphalt surfaces and has high solids for longer protection.



USES:

DEWITT'S DS5000 SUPREME SEALER may be used with complete confidence on any asphalt pavement. DEWITT'S DS5000 SUPREME SEALER is a continuing maintenance requirement for parking lots, driveways, gasoline stations, school yards, airport runways, or anywhere that the asphalt surface is exposed to gas and oil spillage, extensive abrasion, or weathering.

APPLICATION:

DEWITT'S DS5000 SUPREME SEALER can be applied using a brush, squeegee, roller, or mechanical equipment. Do not apply on rainy, foggy, or extremely humid days or when temperature is expected to drop below 40°F during the next 24 hours. For best results, apply in the AM. Allow at least three months for new asphalt to cure before using DEWITT'S DS5000 SUPREME SEALER. Do not use on concrete.

SPECIFICATIONS:

Meets Federal Specifications RP-355-D

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	10 lbs.
Color	Black
Drying time	24 hours at least
Clean up	Mineral Spirits or DEWITT'S Remove-It
Application temperature	40°F

COVERAGE:

One gallon covers 100-125 sq.ft.

PACKAGING:

55 gallon drum, 5 gallon

CAUTION:

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.