



768

# RUBBER SEAL WATER CUT OFF SEALANT

## PRODUCT DESCRIPTION:

RUBBER SEAL WATER CUT OFF SEALANT is a butyl-based, one-component mastic designed specifically for sealing roofing membrane to wood, concrete, metal, plastic, and other substrates. It has high solids content yet remains flexible. Solvent with not attack polystyrene foam.

## USES:

RUBBER SEAL WATER CUT OFF SEALANT can be used to seal roofing membrane terminations and other types of penetrations to prevent water penetration into the roofing system.

## APPLICATION:

RUBBER SEAL WATER CUT OFF SEALANT should be applied at temperatures of 40°F or above. Applying the WATER CUT OFF SEALANT at temperatures below 40°F will extend drying times and potentially cause condensation of water on the sealant bead producing lower ultimate bond strengths. If RUBBER SEAL WATER CUT OFF SEALANT has been stored below 40°F, store the WATER CUT OFF SEALANT at room temperature (72°F) for at least three days before using.

- Insert cartridge into caulk gun, cut nozzle to desired bead size and break seal.
- Extrude bead onto the interface of roofing membrane and other substrate

## PACKAGING:

10.3 oz. cartridge

## PROPERTIES:

### Typical Liquid Properties at 77°F

Base	Butyl
Color	Gray
Total Solids, %	80 minimum
Solvent	Mineral Spirits
Viscosity, cps Brookfield RVT, Helipath, spindle No.TF at 10 rpm	2,900,000
Specific Gravity	1.251
Pounds per Gallon	10.42
Flash Point, °F, (TCC)	>212°F

**HANDLING:**

RUBBER SEAL WATER CUT OFF SEALANT contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from material handling point.

**STORAGE:**

When RUBBER SEAL WATER CUT OFF SEALANT is stored indoors, out of direct sunlight, and in the original, unopened container between 60°F and 80°F, the shelf life is 12 months. Always rotate stock.

DOT Label Required: Flammable UN1133

