

## 103 Foundation and Liquid Roof Coating Material Safety Data Sheet

NDA means No Data Available

Identity (As Used on Label and List) No. 103 Foundation and Liquid Roof Coating	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
Section I				
Manufacturer's Name Address (Number, Street, City, State, and Zip Code)	Telephone Number for Information			
DeWitt Products Company	800-962-8599			
	Telephone Number for Information			
5860 Plumer Ave.	313-554-0575			
	Date Prepared			
Detroit, Michigan 48209	January 2012			
Section II - Hazardous Ingredients/Identity In	formation			
Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS# OSHA PEL ACGIH TLV	%Wt.		
Petroleum Asphalt	8052-42-4			
Petroleum Distillates 64742-48-9				
	ight 0 = Insignificant	azard 0		
Section III - Physical/Chemical Characteristic				
Rolling Doint	Specific Gravity ( $H_2O = 1$ )			
Boiling Point				
NDA	NDA			
NDA Vapor Pressure (mm Hg.)	NDA Melting Point			
NDA Vapor Pressure (mm Hg.) NDA	NDA Melting Point NDA			
NDA Vapor Pressure (mm Hg.)	NDA Melting Point			
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1) NDA	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1)			
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1)	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1)			
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1) NDA Solubility in Water	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1)			
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1) NDA Solubility in Water Insoluble	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1)			
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1) NDA Solubility in Water Insoluble Appearance and Odor A black pourable liquid that smells of petroleum.	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1)			
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1) NDA Solubility in Water Insoluble Appearance and Odor	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1)	UEL		
NDA Vapor Pressure (mm Hg.) NDA Vapor Density (AIR = 1) NDA Solubility in Water Insoluble Appearance and Odor A black pourable liquid that smells of petroleum. Section IV - Fire and Explosion Hazard Data	NDA Melting Point NDA Evaporation Rate (Butyl Acetate = 1) NDA	<b>UEL</b> NDA		

Any approv	ed extinguisher for	oil fires, CO <sub>2</sub> , Dry	Powder, Water Fog.		
Special Fire Fightir	-	<i>.</i>			
If entering a	confined area, fire	efighters should use	e a NIOSGH approved self conta	ained breathing apparatus.	
Unusual Fire and E	xplosion Hazards	5			
None know	n. Do not heat mat	erial. Keep away fro	om heat, open flame, etc.		
Keep lid on	container when no	t in use.			
Section V - Read	ctivity Data				
Stability	Unstable		Conditions to Avoid		
	Stable	X None known			
Incompatibility (Ma	•				
	ct with strong oxid	zers.			
Hazardous Decom	kide - Carbon Mon	ovide			
Hazardous	May Occur	UNICE	Conditions to Avoid		
Polymerization	May Not Occu	r X	None known		
Section VI - Hea	•				
Route(s) of Entry		Inhalation?	Skin?	Ingestion?	
		X	X	X	
and/or liver Ingestion: Carcinogeni	Stomach irritation,	nausea and vomitii NTP?	ng. IARC Monographs?	OSHA Regulated?	
No	0.	NDA	NDA	NDA	
Signs and Sympton	ns of Exposure				
Eyes: Irritat	ion	Skin: Rash	Inhalation: Dizziness, headache	Ingestion: Nausea, vomiting	
Medical Conditions		xposure			
-	ion, eye damage. Could cause dama	age to kidneys, lung	Skin: Rash		
liver.			<sup>1</sup> Ingestion: Could cause inter	rnal organ damage. Seek help.	
Emergency and Fir		S			
Eyes: Flush		:	Skin: Wash area and apply I	otion.	
respiration o		iir, may need artific	ingestion: Do not induce vol	miting, give plenty of fluids.	
		•	o on all above problems.		
Section VII - Pre		<b>U</b>			
Steps to be Taken		-			
material. So			Pump liquids to containers. So ner. Clean up contaminated abs		
Waste Disposal Me					
		according to federa	I, state, and local regulations.		
Precautions to be 1	-	· · · · · · · · · · · · · · · · · · ·			
Store in a container.	cool place away	from excessive he	eat and open flame. Keep aw	ay from children. Keep lid o	
Other Precautions					
مائلات ممال	doguato vontilatio	n Avoid prolonged	d breathing of vapors. Avoid p	violonged skin contact. Do no	

swallow any materia	Ι.				
Section VIII - Control N	leasures				
<b>Respiratory Protection (Sp</b>	ecify Type)				
NIOSH approved ca	rtridge respirator with organi	c vapor cartrid	dge if other controls are not effective.		
Ventilation Local Exhaust	None normally needed.	Special	NDA		
Mechanical (General)	NDA	Other	NDA		
Protective Gloves			Eye Protection		
Rubberized cotton if needed.		Chemical goggles if spraying or splashing occurs.			
Other Protective Clothing of	or Equipment				
A protective apron if	splashing or repeated conta	ct is likely to o	occur.		
Work/Hygienic Practices					
Keep area clean and	d free of hazardous material.				