




110

POLY-PRO COAT

PRODUCT DESCRIPTION:

DEWITT'S POLY-PRO COAT is a specially formulated, fibered asphaltic coating containing refined asphalts, petroleum solvent, and selected hi-tech non-asbestos fibers. The selected hi-tech fibers promote excellent rheology, yet still allow for excellent sprayability and brushability. POLY-PRO COAT penetrates and protects sound roofing felts. Remains pliable and expands and contracts with the change of temperature. Apply directly from container to a variety of roof and outside wall surfaces, shedding water, insulating and preserving.



USES:

DEWITT'S POLY-PRO COAT can be used to resaturate, preserve and protect composition, built-up, smooth and slate surfaced roofs. Can be also used on metal roofs, siding, exterior foundation walls, and other concrete and masonry surfaces. Also use as an interplay adhesive between layers of asphalt felts.

APPLICATION:

Stir if necessary, before use. Surface should be clean, dry and free from all dust or materials. Dried out felts should be primed with DEWITT'S PRO ASPHALT PRIMER (#154). Repair all cracks, breaks, or open seams with DEWITT'S PRO FLASH CEMENT (#251) and reinforcing membrane.

SPECIFICATIONS:

Meets ASTM Specifications D-4479 and Federal Specification SS-A-694D, ASTM D-2823, except this material is asbestos free.

PHYSICAL CHARACTERISTICS:

Weight per gallon (approx)	8lbs
Flash point	100°F Min
Drying time	2-3 days, depending on weather conditions
Viscosity at 80°F	100-120 K.U.

Service temperature, extended exposure	-20° - 150°F
Non-Volatile (Fed. Test Method 141)	62% Min
Percent of specially processed asphalt	58% Min
Percent of total solids by volume	88% Min
Film thickness of 1gal / 100 sq. ft.	8 Mils
Resistance to oils and solvents	Poor
Resistance to sunlight and chemicals	Good
Effects of weathering (ASTM 2823)	Slight Cracking
Water Resistance	
Under good drainage conditions	Excellent
Under continuous submersion	Fair
Clean up	Mineral Spirits or Naphtha
Application temperature	25°- 100°F (Formulated for seasonal use summer grade, spring/fall grade, winter grade)

COVERAGE:

3 gallons per 100 sq. ft. on built up roofs and masonry.
2 gallons per 100 sq. ft. on metal roofs

PACKAGING:

55 gallon drum & 5 gallon pail.

CAUTION:

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.