




203

PRO SBS MODIFIED BITUMEN ADHESIVE

PRODUCT DESCRIPTION:

DEWITT'S PRO SBS MODIFIED BITUMEN ADHESIVE is specially formulated to bond modified asphalt coating membranes together. Its high elastomeric bonding strength and lap strengths far exceed minimum requirements of ASTM D-3019-85 TYPE III. Easy application, low temperature flexibility, and cold application are just some of the many advantages for the applicator. It does not require red label solvent identification, making it easier to store.



USES:

DEWITT'S PRO SBS MODIFIED BITUMEN ADHESIVE is to be used as a cold applied adhesive to bond modified bitumen rolled roofing, such as SBS. DO NOT USE WITH SINGLE PLY TORCHDOWN PRODUCTS. PRO SBS ADHESIVE's elastomeric properties make it an excellent adhesive to adhere composition felts. Use as a flashing cement or anywhere there is a lot of expansion and contraction.

APPLICATION:

Before application, surface must be dry, and free of oil, grease, rust, scale, loose paint, and dirt. Modified Bitumen membrane should be cut in maximum 18' lengths and allowed to relax on the job site. Stir DEWITT'S PRO SBS MODIFIED BITUMEN ADHESIVE before use and apply using a notched squeegee brush, roller, or spray. Apply sufficient adhesive at laps to result in visible bead of adhesive at completed lap edges. Laps must be weighted or rolled after application.

SMOOTH SURFACES - Use notched squeegee with notches 1/4" long, 1/8" wide, spaced on.

IRREGULAR SURFACES - Notch should be 1/4" deep.

SPRAYING - A Spreeflo or Grayco pump capable of delivering 3-5 gallons of mastic coating type material is suitable. A pole gun with a spray tip orifice

(usually .060 mils) is recommended. The material hose should be heavy duty 3/4" I.D. A 1/2" I.D. air hose from pump to gun is preferred.

SPECIFICATIONS:

Meets ASTM D-3019-85 TYPE III.

PHYSICAL CHARACTERISTICS:

Weight per gallon (approx)	7.8 lbs
Total solids	58%
Consistency appearance	Squeegee, brush, or spray
Dry film	Glossy black, fibrous
Suspendability	Will settle slightly
Aging	Indefinite if in an air tight container
Clean up	Mineral Spirits, Naphtha, Kerosene

COVERAGE:

Average application rate is 1.5 gallons per 100 sq. ft.

PACKAGING:

55 gallon drum, & 5 gallon pail.

CAUTION:

Combustible: Keep away from heat and open flame. Avoid prolonged contact with skin and breathing vapor or spray mist. Do not take internally. Close container after each use. Use only with adequate ventilation. Keep out of reach of children.