



319

COOL-TOP WHITE SP MASTIC 650

PRODUCT DESCRIPTION:

DEWITT'S COOL-TOP WHITE SP MASTIC 650 is a solvent-based Terpolymer sealant manufactured from synthetic elastomers, adhesive resins and polyolefin micro-fibers for reinforcement. Consistency is a medium viscosity mastic flashing grade that is high-bodied for application to vertical surfaces with no sagging. Extremely strong and elastic. High elongation and tensile strength insure performance under conditions that will cause asphalt-based cements to fail. Unique surface active additives allow application to wet or underwater surfaces. Use on most roofs wet or dry.

USES:

DEWITT'S COOL-TOP WHITE SP MASTIC 650 can be used for the repair of asphalt, modified bitumen, metal, Kynar®, concrete, TPO, PVC, Elvaloy®/PVC, Hypalon® (CSPE), PIB and EPDM roofs. DEWITT'S COOL-TOP WHITE SP MASTIC 650 is the ideal maintenance and repair product for all roofs in all weather.

APPLICATION:

Surface must be clean and sound. Apply with a roofer's trowel 1/8" thick. Taper edges of the repair to a smooth edge. Polyester fabric may be embedded for added strength. When applying to wet surfaces, pressure is required to displace moisture and insure proper adhesion. Over-application on EPDM roofs may cause swelling of the EPDM. Clean up with mineral spirits or #414 DeWitt's Remove-It.

PHYSICAL CHARACTERISTICS:

Recommended rate of application	1/8" thick
% Solids by volume	49 min
% Non-volatile	55 max
VOC	Less than 550g/l
Elongation	300% @ 77°F (25°C)
Flash Point (TCC)	+100°F (38.7°C)
Color	White or Black

PACKAGING:

1 gallon, 3 gallon

CAUTION:

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed. Avoid prolonged contact with skin or fumes.