



402

PRO MASTIC 55

DAMPPROOF COATING (Trowel-On)

PRODUCT DESCRIPTION:

DEWITT'S PRO MASTIC 55 DAMPPROOF COATING (trowel grade) is a superior asphalt mastic, reinforced with non-asbestos high-tech fibers. DEWITT'S PRO MASTIC 55 DAMPPROOF COATING (trowel grade) is a multi-purpose, cold applied cement, that offers very high vapor barrier efficiency. This heavy bodied mastic produces a waterproof membrane to protect masonry surfaces above and below grade. When applied to foundations it will withstand chemical and alkali attack from ground waters. DEWITT'S PRO MASTIC 55 DAMPPROOF COATING (trowel grade) resists alkali attack from lime, gypsum, or Portland cement systems.



USES:

DEWITT'S PRO MASTIC 55 DAMPPROOF COATING (trowel grade) can be used above or below ground for stone backing, floor and wall membrane, steel protection and related applications.

APPLICATION:

DEWITT'S PRO MASTIC 55 DAMPPROOF COATING (trowel grade) is used directly from the container. Apply with a trowel or putty knife to surfaces that must be free of dirt, dust and debris. Apply DEWITT'S PRO MASTIC 55 DAMPPROOF COATING (trowel grade) at 1/16" - 1/8" thick.

SPECIFICATIONS:

Meets ASTM 4586-86 and Federal Specification SS-C-153C ASTM D-2822 Type I, except this material is asbestos free.

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	9 lbs.
Flash point (ASTM 093-52)	100° F Min
Drying time	2-3 days, depending on weather conditions
Viscosity at 80° F	Medium to heavy trowel
Service temperature, extended exposure	-40° to 180° F
Resistance to oils and solvents	Poor
Resistance to sunlight	Excellent
Resistance to chemicals	Excellent
Effects of weathering	Minimal
Water Resistance	
Under draining conditions	Excellent
Under continuous submersion	Fair
Restrictions	Do not use on tar roofs
Clean up	Mineral Spirits, Naphtha or DEWITT'S REMOVE-IT
Application temperature	25°-100° F (formulated for seasonal use: summer grade, fall/spring grade, winter grade)

COVERAGE:

One gallon covers approximately 7 sq. ft. at 1/4" thick.

PACKAGING:

55 gallon drum, 5 gallon

CAUTION:

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.