



405

IRON & TANK PAINT

PRODUCT DESCRIPTION:

DEWITT'S IRON AND TANK PAINT is a product of asphalt and other waterproofing agents. DEWITT'S IRON AND TANK PAINT will protect any type of exterior metal surface against rust and other deterioration.



USES:

DEWITT'S IRON AND TANK PAINT can be used wherever waterproofing is required. A high melting point makes DEWITT'S IRON AND TANK PAINT an excellent asphalt paint for metal because it will stand up against the heat of the sun's rays without becoming soft.

APPLICATION:

DEWITT'S IRON AND TANK PAINT can be applied using a brush, squeegee, roller or mechanical equipment. Do not apply on rainy, foggy or extremely humid days or when temperatures are expected to drop below 15°F during the next 24 hours.

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	7.9 lbs.
Flash point (ASTM 093-52)	100° F Min
Drying time	2-3 hours
Viscosity at 80° F	200-250 cps
Service temperature, extended exposure	-20° to 150° F
Resistance to oils and solvents	Poor
Resistance to sunlight	Good
Resistance to chemicals	Good

Water Resistance	
Under draining conditions	Good
Under continuous submersion	Fair
Clean up	Mineral Spirits, Naphtha or DEWITT'S REMOVE-IT
Application temperature	-55°-90° F

COVERAGE:

One gallon covers approximately 100-125 sq. ft.

PACKAGING:

55 gallon drum, 5 gallon

CAUTION:

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.