



406

VAULT SEAL

VAULT AND SEPTIC TANK SEALER

PRODUCT DESCRIPTION:

DEWITT'S VAULT SEAL is a high grade bituminous plastic sealer for concrete burial vaults or for any application where a superior sealer must be used to seal a joint against moisture such as acid and alkali resistant burial vaults, manhole covers, septic tanks, etc. DEWITT'S VAULT SEAL is trowel grade consistency.



USES:

DEWITT'S VAULT SEAL can be used on burial vaults, manhole covers, septic tanks, etc.

APPLICATION:

DEWITT'S VAULT SEAL can be used directly from the container. Apply with a trowel or putty knife. Surfaces must be free of dirt, dust and debris. Apply 1/8" - 1/2" thick.

SPECIFICATIONS:

Meets ASTM 4586-86 and Federal Specification SS-C-153C ASTM D-2822 Type I, except this material is asbestos free.

PHYSICAL CHARACTERISTICS:

Weight per gallon (approx.)	9 lbs
Flash Point (ASTM 093-52)	100°F min
Drying Time	2-3 days, depending on weather conditions
Viscosity at 80°F	Medium to heavy trowel
Service Temp, extended exposure	-40° to 180°F
Resistance to oils and solvents	Poor
Resistance to sunlight	Excellent
Resistance to chemicals	Excellent
Effects of weathering	Minimal
Water Resistance	

Under draining conditions	Excellent
Under continuous submersion	Fair
Restrictions	Do not use on COAL TAR, EPDM, PVC or TPO roofs
Clean Up	Mineral spirits, DeWitt's REMOVE-IT
Application Temperature	25° - 100°F

COVERAGE:

One gallon covers approximately 7 sq. ft. at 1/4" thick.

PACKAGING:

55 gallon drum, 5 gallon

CAUTION:

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.

