




505

# DS1500 PLUS

## CRACK FILLER (Trowel-On)

### PRODUCT DESCRIPTION:

DEWITT'S DS1500 PLUS CRACK FILLER is a thick blend of asphalt and fillers for heavy duty repairs.



### USES:

DEWITT'S DS1500 PLUS CRACK FILLER can be used to fill expansion joints and wide cracks, up to 1" wide, or any job requiring a trowel-grade crack filler.

### APPLICATION:

DEWITT'S DS1500 PLUS CRACK FILLER comes ready to use. Apply using a putty knife or mason's trowel. Keep material in crack and level with surface. For best results, apply on dry surface when temperature is not expected to drop below 40°F during the next 24 hours. DO NOT APPLY if rain is expected.

### SPECIFICATIONS:

Meets ASTM D-244 ands ASTM M-140-70

### PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	9 lbs.
Color	Black
Drying time	24-48 hours
Clean up	Mineral Spirits or DEWITT'S Remove-It
Application temperature	Above 40°F

**COVERAGE:**

Coverage will vary with size and depth of crack.

**PACKAGING:**

5 gallon, 1gallon & 10.2oz cartridge.

**CAUTION:**

Combustible: Keep away from heat and open flame.

Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.