



508

DS1200 PLUS

CRACK FILLER (Asphalt Emulsion)

PRODUCT DESCRIPTION:

DEWITT'S DS1200 ULTRA FLEX CRACK FILLER is a super rubberized crack filler that is fortified with polymers and select mineral fillers. Formulated to last longer than standard crack filler. Fills cracks and small holes up to 3/8" in width in pavement of all types. DEWITT'S DS1200 ULTRA FLEX CRACK FILLER is a rich black color to blend in with asphalt pavements. Reduces and retards erosion and other damages caused when cracks and holes remain unrepaired. Helps to prolong a pavement's life with proper periodic maintenance. For holes and cracks greater than 3/8" and up to 1" use DEWITT'S #505 DS1500 TROWEL GRADE CRACK FILLER. For holes and cracks greater than 1" in width, use DEWITT'S #506 ASPHALT PRO PATCH.



USES:

DEWITT'S DS1200 ULTRA FLEX CRACK FILLER can be used to fill crack 3/8" wide or less. DEWITT'S DS1200 ULTRA FLEX CRACK FILLER can be used on cracks in concrete, asphalt driveways and parking areas.

APPLICATION:

DEWITT'S DS1200 ULTRA FLEX CRACK FILLER is packaged ready to use. Clean all cracks free of dust, dirt, and debris by broom, water spray or power blower. Assure all cracks are free of puddle water, vegetation and existing crack filler. Fill deep cracks to 3/4" from surface with sand or rope. Shake container well before use. Cut spout tip to accommodate crack size. Place spout tip above crack, squeeze out crack filler while drawing spout along crack. Keep material in crack, at or below surface, since crack filler remains flexible. Over application may cause scuffing and tracking. A second application can be made if necessary. Allow 24 hours between applications. For best results, apply on dry surface when temperature is not expected to drop below 40°F during the next 24 hours. DO NOT APPLY if rain is expected.

PHYSICAL CHARACTERISTICS:

Weight per gal. (approx)	9 lbs.
Color	Black
Drying time	24 - 48 hours
Clean up	Mineral Spirits or DEWITT'S Remove-It
Application temperature	Above 40°F

COVERAGE:

150 linear feet at 1/4" and 1/4" deep per gallon

PACKAGING:

1 gallon, 5 gallon

CAUTION:

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.