



710-715

# RUBBER SEAL EPDM COVER STRIP

Step 3

## PRODUCT DESCRIPTION:

DEWITT'S RUBBER SEAL EPDM COVER STRIP is a self-adhesive fully cured EPDM roll that instantly seals and waterproofs tears, holes, and punctures. Installs fast and easy which saves time and money. DEWITT'S RS EPDM COVER STRIP can be applied from -15° F to 150°F. This butyl based tape results in high strength and flexibility over a broad temperature range. DEWITT'S RS EPDM COVER STRIP does not absorb moisture, and will not peel, shrink, or crack. Permanently bonds to most surfaces and will last 35 years or more when properly applied.



## USES:

DEWITT'S RS EPDM COVER STRIP can be used to repair EPDM, CSPE/Hypalon, APP/SBS modified, TPO, most PVC, asphalt BUR, shingles, tile, metal roofs, and much more. DEWITT'S RS EPDM COVER STRIP can also be used for sealing skylights, gutters, coping, metal and polymeric fastening plates, termination bars, gravel stop flashings, ductwork, PVC pipe, awnings, tents, tarps, RV's, tanks, and other air leaks. It adheres to most types of roofing membrane, painted and unpainted metal, wood, glass, brick, concrete, plastic, OSB board, ceramic, gypsum board, polystyrene, vinyl siding, canvas, and fiberglass.

## APPLICATION:

1. Clean area with DEWITT'S #700 RS ROOF CLEANER.
2. Prime the area with DEWITT'S #701 RS ROOF PRIMER.
  - Unroll 12" of DEWITT'S RS EPDM COVER STRIP with release side up and place at one end of the repair area.
  - Peel back 8" of paper to expose adhesive side of strip. Fold adhesive side back under onto the starting point.

- Peel off additional paper until entire outside surface of roll is exposed adhesive.
- Place knee on paper and thumb in each end of roll core and push roll down repair area.
- Use seam roller over entire area moving roller both parallel and perpendicular over patched area.

### PHYSICAL CHARACTERISTICS:

|                       |  |
|-----------------------|--|
| Base                  | Butyl Rubber                           |
| Color                 | Black or White                         |
| Odor                  | Slight hydrocarbon                     |
| Tensile. psi          | 100                                    |
| Elongation %          | 1200                                   |
| Flashpoint            | 450°F                                  |
| Density               | 10.4±0.1                               |
| Volatile, % by volume | <1%                                    |
| Adhesion              | To most clean, dry substrates/surfaces |

### PACKAGING:

Rolls, available in black or white.

5" x 25'      6" x 100'      5" x 100'

### CAUTION:

This product contains ingredients which could be harmful if misused. Avoid contact with skin and eyes. Protective clothing should be used when handling this product.