



730-732

RUBBER SEAL EPDM SEAM TAPE

PRODUCT DESCRIPTION:

DEWITT'S RS EPDM SEAM TAPE is a black, butyl rubber based adhesive in tape form. DEWITT'S RS EPDM SEAM TAPE has high green strength in peel and shear.

USES:

DEWITT'S RS EPDM SEAM TAPE is for commercial construction with EPDM, PIB, TPO, Neoprene, Hypalon, & PVC roofing systems. This product may also be used for underwater waste and fish ponds.

APPLICATION:

1. Clean area with DEWITT'S #700 RS ROOF CLEANER (if needed)
2. Prime the area with DEWITT'S #701 RS ROOF PRIMER (if needed)
3. Apply tape and use seam roller over entire area, moving roller both parallel and perpendicular over the patched area.

PHYSICAL CHARACTERISTICS:

| | |
|-------------------------|---------------|
| Base | Butyl Rubber |
| Color | Black |
| Tensile PSI | 55 |
| Elongation % | 750 |
| Peel Strength, PSI | 15 min |
| Permeability | 0.6 perm-mils |
| Brittleness Temperature | -50°F |

PACKAGING:

Black roll 3" x 25' Black roll 3" x 50' Black roll 3" x 100'

CAUTION:

This product contains ingredients which could be harmful if misused. Avoid contact with skin and eyes. Protective clothing should be used when handling this product.

