



764

# RUBBER SEAL SPLICE CLEANER

---

## **PRODUCT DESCRIPTION:**

RUBBER SEAL SPLICE CLEANER is designed for thorough cleaning of single-ply membrane splices prior to the application of primers or splice adhesives.

## **USES:**

RUBBER SEAL SPLICE CLEANER can be used to clean EPDM, Neoprene, CPE, and other single-ply membranes.

## **APPLICATION:**

RUBBER SEAL SPLICE CLEANER should be applied at temperatures of 40°F or above. Applying the cleaner at temperatures below 40°F will extend drying times and potentially cause condensation of water on the membrane surface producing lower ultimate bond strengths. If RUBBER SEAL SPLICE CLEANER is stored below 40°F, store the cleaner at room temperature (72°F) for at least three days before using.

RUBBER SEAL SPLICE CLEANER should be applied with clean, lint-free rags. Change cleaning rags frequently.

## **PACKAGING:**

1 gallon, 5 gallon

## **HANDLING:**

RUBBER SEAL SPLICE CLEANER contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. All 5 gallon pails should be grounded and/or bonded when material is transferred. Vapors are heavier than air and may travel along the ground or may be moved by

ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from material handling point.

**STORAGE:**

When RUBBER SEAL SPLICE CLEANER is stored indoors, out of direct sunlight, and in the original, unopened container between 60°F and 80°F, the shelf life is twelve months. Always rotate stock.

