



765

RUBBER SEAL SEAM/TAPE WASH-PRIMER

PRODUCT DESCRIPTION:

RUBBER SEAL SEAM/TAPE WASH-PRIMER is a solvent-based primer designed to be used to prepare surfaces of single-ply membrane for bonding with RUBBER SEAL tape products and RUBBER SEAL adhesives for commercial roofing. It can be used as a wash to clean and prime single-ply membrane in one operation or it can be brushed on to membrane that has been previously cleaned with approved cleaning agent such as #764 RUBBER SEAL SPLICE CLEANER.

- Fast drying
- Curing system gives improved cohesive strength
- Increases adhesion of RUBBER SEAL adhesive/sealant products to single-ply membrane

USES:

RUBBER SEAL SEAM/TAPE WASH-PRIMER was specifically developed for use with EPDM single-ply roofing membrane. However, it may be used with most types of roofing membrane as well as to other materials used in construction including painted and unpainted metals, brick, ceramic, wood, rubber, vinyl, and concrete.

APPLICATION:

Solids suspended in RUBBER SEAL SEAM/TAPE WASH-PRIMER tend to settle and must be stirred before and during use. RUBBER SEAL SEAM/TAPE WASH-PRIMER should be used full strength. **DO NOT DILUTE.**

RUBBER SEAL SEAM/TAPE WASH-PRIMER should be applied at a temperature of 40°F or above. Applying the primer at temperatures below 40°F will extend drying times and potentially cause condensation of water on the primer film producing lower ultimate bond strengths. If RUBBER SEAL SEAM/TAPE WASH-PRIMER is stored below 40 °F, store the primer at room temperature (72°F) for at least three days before using.

When using RUBBER SEAL SEAM/TAPE WASH-PRIMER to clean and prime in one operation, scrub the surface of the membrane with a clean scrub pad or rag saturated with the RUBBER SEAL SEAM/TAPE WASH-PRIMER. Membrane surfaces should appear wet while scrubbing. Apply the RUBBER SEAL SEAM/TAPE WASH-PRIMER to an area wider than the actual width being bonded to insure bonding to primed surfaces. When the rag or scrub pad becomes dirty, discard appropriately and use a fresh one. The primed surface must be dry to the touch before RUBBER SEAL tape

products or RUBBER SEAL adhesives can be applied.

RUBBER SEAL SEAM/TAPE WASH-PRIMER can be applied with a scrub pad, a brush, or lint-free cloth on membrane that has been previously cleaned with an approved cleaning agent.

PACKAGING:

1 gallon, 5 gallon

HANDLING:

RUBBER SEAL SEAM/TAPE WASH-PRIMER contains ingredients which could be harmful if mishandled. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. All 5 gallon pails should be grounded and/or bonded when material is transferred. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at location distant from material handling point.

STORAGE:

When RUBBER SEAL SEAM/TAPE WASH-PRIMER is stored indoors, out of direct sunlight, and in the original, unopened container between 60°F and 80°F, the shelf life is nine months. Always rotate stock.