



PRODUCT CODE: 152

# PRO WET-STICK FIBERED ROOF COATING

## DESCRIPTION

DEWITT'S PRO WET-STICK FIBER ROOF COATING is an all purpose roof coating manufactured with special blend asphalt, refined oils, mineral stabilizers and reinforced with hi-tech asbestos-free fibers. DEWITT'S PRO WET-STICK FIBER ROOF COATING sets up to form a tough, continuous, moisture-proof film that will retain its pliability for a long period of time. This enables it to expand and to conform to movement of other materials. DEWITT'S PRO WET-STICK FIBER ROOF COATING penetrates and protects sound roofing felts. Remains pliable, expands and contracts with the change of temperature. Apply directly from can to a variety of roof and outside wall surfaces, shedding water, insulating and preserving. DEWITT'S PRO WET-STICK FIBER ROOF COATING can be used on wet or dry surfaces.

## USES

DEWITT'S PRO WET-STICK FIBER ROOF COATING can be used to resaturate, preserve, and protect composition, built-up, smooth, and slate surfaced roofs. DEWITT'S PRO WET-STICK FIBER ROOF COATING can also be used on metal roofs, siding, exterior foundation walls, and other concrete and masonry surfaces. Also use as an inter-ply adhesive between layers of asphalt felts. Do not use on COAL TAR, EPDM, TPD, or PVC type roofs. This product can be used on SBS Modified roofs.

## APPLICATION

Stir if necessary before use. Surface should be clean, free of all dirt, dust, debris, and materials. Dried out felts should be primed with DEWITT'S #154 ASPHALT PRIMER. Repair all cracks, breaks, or open seams with DEWITT'S #252 WET-STICK ROOF CEMENT, DEWITT'S #253 PRO FLASH XTRA, or DEWITT'S #251 PRO FLASH.

## SPECIFICATIONS

Meets ASTM Specifications D-4479-85 and Federal Specifications SS-A-694D, except this material is asbestos free.

## COVERAGE

1 ½ -2 gallons per 100 sq. ft. on built-up roofs and masonry.  
1 gallons per 100 sq. ft. on metal roofs

## PACKAGING

55 gallon drum, 5 gallon & 1 gallon.

## CAUTION

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.



## PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	8 lbs
FLASH POINT (ASTM 093-52)	100° F Min
DRYING TIME	2-3 days, depending on weather conditions
VISCOSITY AT 80° F	100 - 120 K.U.
SERVICE TEMPERATURE (EXTENDED EXPOSURE)	-20° to 150° F
NON-VOLITILE (FED. TEST METHOD 141)	62% Min
PERCENT OF SPECIALLY PROCESSED ASPHALT	58% Min
PERCENT OF TOTAL SOLIDS BY VOLUME	88% Min
FILM THICKNESS OF .1GAL/100 SQ. FT.	8 Mills
RESISTANCE TO OILS AND SOLVENTS	Poor
RESISTANCE TO SUNLIGHT AND CHEMICALS	Excellent
SPECIFIC GRAVITY AT 77° F	.427
WATER RESISTANCE	
UNDER DRAINING CONDITIONS	Excellent
UNDER CONTINUOUS SUBMERSION	Fair
CLEAN UP	Mineral Spirits or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	25°-100° F (formulated for seasonal use: summer grade, fall/ spring grade, winter grade)