



PRODUCT CODE: 405

# IRON AND TANK PAINT

## DESCRIPTION

DEWITT'S IRON AND TANK PAINT is a product of asphalt and other waterproofing agents. DEWITT'S IRON AND TANK PAINT will protect any type of exterior metal surface against rust and other deterioration.

## USES

DEWITT'S IRON AND TANK PAINT can be used wherever waterproofing is required. A high melting point makes DEWITT'S IRON AND TANK PAINT an excellent asphalt paint for metal because it will stand up against the heat of the sun's rays without becoming soft.

## APPLICATION

DEWITT'S IRON AND TANK PAINT can be applied using a brush, squeegee, roller or mechanical equipment. Do not apply on rainy, foggy or extremely humid days or when temperatures are expected to drop below 15° F during the next 24 hours.

## COVERAGE

One gallon covers approximately 100-125 sq. ft.

## PACKAGING

55 gallon drum & 5 gallon pails

## CAUTION

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.



## PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	7.9 lbs
FLASH POINT (ASTM 093-52)	100° F Min
DRYING TIME	2-3 hours
VISCOSITY AT 80° F	200-250 cps
SERVICE TEMPERATURE (EXTENDED EXPOSURE)	-20° to 150° F
RESISTANCE TO OILS AND SOLVENTS	Poor
RESISTANCE TO SUNLIGHT AND CHEMICALS	Good
EFFECTS OF WEATHERING	Minimal
WATER RESISTANCE	
UNDER DRAINING CONDITIONS	Excellent
UNDER CONTINUOUS SUBMERSION	Fair
RESTRICTION	Do not use on tar roofs
CLEAN UP	Mineral Spirits, Naphtha, or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	-55° -90° F