



PRODUCT CODE: 406

VAULT SEAL VAULT AND SEPTIC TANK SEALER

DESCRIPTION

DEWITT'S VAULT SEAL is a high grade bituminous plastic sealer for concrete burial vaults or for any application where a superior sealer must be used to seal a joint against moisture such as acid and alkali resistant burial vaults, manhole covers, septic tanks, etc. DEWITT'S VAULT SEAL is trowel grade consistency.

USES

DEWITT'S VAULT SEAL can be used on burial vaults, manhole covers, septic tanks, etc.

APPLICATION

DEWITT'S VAULT SEAL can be used directly from the container. Apply with a trowel or putty knife. Surfaces must be free of dirt, dust and debris. Apply 1/8" - 1/2" thick.

SPECIFICATIONS

Meets ASTM 4586-86 and Federal Specification SS-C-153C ASTM D-2822 Type I, except this material is asbestos free.

COVERAGE

One gallon covers approximately 7 sq. ft. at 1/4" thick.

PACKAGING

55 gallon drum & 5 gallon pails

CAUTION

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	9 lbs
FLASH POINT (ASTM 093-52)	100° F Min
DRYING TIME	2-3 days, depending on weather conditions
VISCOSITY AT 80° F	Medium to heavy trowel
SERVICE TEMPERATURE (EXTENDED EXPOSURE)	-20° to 150° F
RESISTANCE TO OILS AND SOLVENTS	Poor
RESISTANCE TO SUNLIGHT AND CHEMICALS	Excellent
EFFECTS OF WEATHERING	Minimal
WATER RESISTANCE	
UNDER DRAINING CONDITIONS	Excellent
UNDER CONTINUOUS SUBMERSION	Fair
RESTRICTION	Do not use on COAL TAR, EPDM, PVC or TPO roofs
CLEAN UP	Mineral Spirits or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	25° - 100° F