



PRODUCT CODE: 503

DS 4000 PLUS DRIVEWAY FILLER AND SEALER

DESCRIPTION

DEWITT'S DS4000 PLUS DRIVEWAY FILLER AND SEALER is an improved, heavy duty asphalt emulsion driveway sealer manufactured by colloidal mill process and fortified with rubber for added pavement adhesion, and non-discoloring graded aggregated for increased traction and longer life. DEWITT'S DS4000 PLUS FILLER AND DRIVEWAY SEALER seals out weather's destructive elements and protects against damaging effects of gasoline, oil drippings and salt. DEWITT'S DS 4000 DRIVEWAY SEALER also will fill small voids in asphalt surfaces. Especially good for sloping surfaces.

USES

DEWITT'S DS4000 PLUS DRIVEWAY FILLER AND SEALER may be used with complete confidence on any asphalt pavement. DEWITT'S DS4000 PLUS DRIVEWAY FILLER AND SEALER is a continuing maintenance requirement for parking lots, driveways, gasoline stations, school yards, airport runways, or anywhere that the asphalt surface is exposed to gas and oil spillage, extensive abrasion, or weathering extremes.

APPLICATION

DEWITT'S DS4000 PLUS DRIVEWAY FILLER AND SEALER can be applied using a brush, squeegee, roller, or mechanical equipment. Do not apply on rainy, foggy, or extremely humid days or when temperature is expected to drop below 40° F during the next 24 hours. For best results, apply in the AM. Allow at least three months for new asphalt to cure before using DEWITT'S DS4000 PLUS DRIVEWAY FILLER AND SEALER. Do not use on concrete surfaces.

SPECIFICATIONS

Meets Federal Specifications RP-355-D

COVERAGE

One gallon covers approximately 100-125 sq. ft.



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	10 lbs
COLOR	Black
DRYING TIME	24 hours at least
CLEAN UP	Mineral Spirit or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	Above 50° F

PACKAGING

55 gallon drum, 5 gallon

CAUTION

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.