



PRODUCT CODE: 504

DS 1000 PLUS CRACK FILLER (ASPHALT BASE)

DESCRIPTION

DEWITT'S DS1000 PLUS CRACK FILLER is a special blend of liquid asphalt, rubber, plasticizers and fillers for do-it-yourself repair of cracks and expansion joints in concrete, asphalt driveways, and parking areas. DEWITT'S DS1000 PLUS CRACK FILLER forms a tough, elastic sealer strip.

USES

DEWITT'S DS1000 PLUS CRACK FILLER can be used to fill cracks 3/8" wide or less. DEWITT'S DS1000 PLUS CRACK FILLER can be used on cracks in concrete, asphalt driveways, and parking areas.

APPLICATION

Place spout tip above crack. Squeeze out DEWITT'S DS1000 PLUS CRACK FILLER while drawing spout along crack. Keep material in crack level with surface. For best results, apply on dry surface when temperature is not expected to drop below 40° F during the next 24 hours. DO NOT APPLY if rain is expected.

SPECIFICATIONS

Meets ASTM D-244 and ASTM M-140-70

COVERAGE

150 linear feet at 1/4" and 1/4" deep per gallon

PACKAGING

55 gallon drum, 5 gallon, 1 gallon



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	10 lbs
COLOR	Black
DRYING TIME	24 - 48 hours
CLEAN UP	Mineral Spirit or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	Above 50° F

CAUTION

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.