



PRODUCT CODE: 505

# DS 1500 PLUS CRACK FILLER (TROWEL- ON)

## DESCRIPTION

DEWITT'S DS1500 PLUS CRACK FILLER is a thick blend of asphalt and fillers for heavy duty repairs.

## USES

DEWITT'S DS1500 PLUS CRACK FILLER can be used to fill expansion joints and wide cracks, up to 1" wide, or any job requiring a trowel-grade crack filler.

## APPLICATION

DEWITT'S DS1500 PLUS CRACK FILLER comes ready to use. Apply using a putty knife or mason's trowel. Keep material in crack and level with surface. For best results, apply on dry surface when temperature is not expected to drop below 40° F during the next 24 hours. DO NOT APPLY if rain is expected.

## SPECIFICATIONS

Meets ASTM D-244 and ASTM M-140-70

## COVERAGE

Coverage will vary with size and depth of crack.

## PACKAGING

5 gallon, 1gallon & 10.2oz cartridge.

## CAUTION

Combustible: Keep away from heat and open flame. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.



## PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	9 lbs
COLOR	Black
DRYING TIME	24 - 48 hours
CLEAN UP	Mineral Spirit or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	Above 40° F