



PRODUCT CODE: 512

DS1200 LEVELING 'N' CRACK PATCH

DESCRIPTION

DEWITT'S LEVELING 'N' CRACK PATCH is a heavily fortified homogenous mixture of rubber, liquid asphalt, and mineral filler. Apply to roofs (built-up metal, SBS) or black top driveways that have shallow depressions that hold water. DEWITT'S LEVELING 'N' CRACK PATCH when used as specified will create positive water drainage which will prolong driveway and roof life.

USES

DEWITT'S LEVELING 'N' CRACK PATCH can also be used to fill medium-sized cracks.

APPLICATION

Remove all dirt, dust, debris, and grease from surfaces and cracks. DEWITT'S LEVELING 'N' CRACK PATCH is ready to use. Apply with pointed trowel, dipping trowel in water frequently. Do not apply if temperature is to go below 40° F.

BLACKTOP DRIVEWAYS: Apply at 1/4"-3/8" thickness. If depression is deeper, apply in layers. Make sure each layer is completely dry and hard before applying succeeding layers. On last layer, level it off and smooth with wet trowel to a feathered edge. Once cured, apply one of DEWITT'S DRIVEWAY SEALERS (DS2000, DS4000, DS5000 or DS6000) to entire surface to protect from sun, weather, oil, and fuel.

ROOFS: Apply the same way as stated for the driveways. Once cured, apply DEWITT'S polyester cotton or fiberglass membrane over patched area with DEWITT'S #251 PRO FLASH ROOF CEMENT or #252 PRO WET-STICK ROOF CEMENT. Coat entire surface with DEWITT'S #151 PRO FIBER ROOF COATING or DEWITT'S ALUMINUM COATINGS.

PACKAGING

1 gallon

CAUTION

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	9.67 lbs
COLOR	Black
DRYING TIME	24 hours at least
CLEAN UP	Mineral Spirits or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	40° F