



PRODUCT CODE: 508

# DS 1200 PLUS CRACK FILLER

## DESCRIPTION

DS1200 ULTRA FLEX CRACK FILLER is a contractor-grade, polymer-fortified emulsion designed to fill cracks and small holes up to 3/8" wide in virtually any pavement type. Its deep black finish blends seamlessly with asphalt surfaces, leaving repairs clean and nearly invisible. Engineered to outlast standard fillers, DS1200 ULTRA FLEX helps stop erosion in its tracks, sealing out moisture and preventing damage from expanding cracks. Regular use as part of your maintenance plan can extend pavement life by years, saving you the cost of major repairs.

Need to repair larger cracks? Use:

DEWITT'S #505 DS1500 Trowel Grade Crack Filler for cracks from 3/8" to 1" wide

DEWITT'S #506 Asphalt Pro Patch for holes and cracks over 1" wide

Whether you're sealing a driveway, parking lot, or sidewalk, DS1200 delivers long-lasting flexibility and protection in any climate.

## USES

DS1200 ULTRA FLEX CRACK FILLER can be used to fill crack 3/8" wide or less in concrete and asphalt driveways.

## APPLICATION

DS1200 ULTRA FLEX CRACK FILLER is packaged ready to use. Clean all cracks free of dust, dirt, and debris by broom, water spray or power blower. Assure all cracks are free of puddle water, vegetation and existing crack filler. Fill deep cracks to 3/4" from surface with sand or rope. Shake container well before use. Cut spout tip to accommodate crack size. Place spout tip above crack, squeeze out crack filler while drawing spout along crack. Keep material in crack, at or below surface, since crack filler remains flexible.

Over application may cause scuffing and tracking. A second application can be made if necessary. Allow 24 hours between applications. For best results, apply on dry surface when temperature is not expected to drop below 40° F during the next 24 hours. DO NOT APPLY if rain is expected.

## COVERAGE

150 linear feet at 1/4" and 1/4" deep per gallon



## PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	9 lbs
COLOR	Black
DRYING TIME	24 - 48 hours
CLEAN UP	Mineral Spirit or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	Above 40° F

## PACKAGING

5 gallon and 1 gallon

## CAUTION

**DO NOT ALLOW TO FREEZE.** Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.