



PRODUCT CODE: 518

D-MAX DRIVE SHIELD ASPHALT EMULSION

DESCRIPTION

D-MAX DRIVE SHIELD ASPHALT EMULSION is a formulated, heavy duty asphalt emulsion driveway sealer that is polymer fortified for added pavement adhesion. D-MAX DRIVE SHIELD features a proprietary patented aggregate blend which we've engineered for superior traction, durability, and finish, giving us an edge over our competitors by ensuring long-lasting protection and a jet black look that stands out from other sealers.

USES

D-MAX DRIVE SHIELD may be used with complete confidence on any asphalt pavement. It is a continuing maintenance requirement for parking lots, driveways, gas stations, school yards, airport runways, or anywhere that the asphalt surface is exposed to gas and oil spillage, extensive abrasion, or weathering.

APPLICATION

D-MAX DRIVE SHIELD can be applied using a brush, squeegee, roller, or mechanical equipment. Do not apply on rainy, foggy, or extremely humid days. For best results, apply in the morning. Allow at least three months for new asphalt to cure before using D-MAX DRIVE SHIELD. Do not use on concrete.

SPECIFICATIONS

Meets Federal Specifications RP-355-D

COVERAGE

One gallon covers 100-125 sq.ft.



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	8.5 - 9 lbs
COLOR	Jet black
DRYING TIME	2 - 6 hours
CLEAN UP	Mineral Spirit or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	Above 40° F
QUV UV TEST (1,000 HOURS)	No Visible Fading

PACKAGING

55 gallon drums, 5 gallon pails, or bulk

CAUTION

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.