



PRODUCT CODE: 321

COOL-TOP WHITE SILICONE MASTIC

DESCRIPTION

DeWitt's COOL-TOP White Silicone Mastic is a single part flashing sealant that can be used on roof fasteners, transitions, seams, and penetrations to seal, protect, or repair various roof types. DeWitt's COOL-TOP White Silicone Mastic is strong and durable, retaining its strength even on penetrations and fasteners with movement. It is weatherproof, does not degrade in sunlight, and is mold and mildew resistant. Its high flexibility and brilliant white color give roofs longer life, saves energy and provides cooler interior temperatures.

USES

DEWITT'S COOL-TOP White Silicone Mastic can be used on concrete, metal, and most substrates.

APPLICATION

Surface to be coated must be dry and free of debris, and should be between 40° F and 120° F. Roof temperature should be above freezing during application. Always test adhesion before applying to different substrates. Use COOL-TOP WHITE Silicone Mastic as it comes from the container, no thinning or mixing necessary. Apply an even coat of COOL-TOP WHITE Silicone Mastic to extend a minimum of 4" over the surface of the roof. Coverage may vary depending on application method and type of substrate involved. COOL-TOP WHITE Silicone Mastic can be applied in a single coat. Curing time will vary depending on temperature and humidity.

COVERAGE

Coverage varies depending on roofing type.

PACKAGING

1 & 2.5 gallon buckets

CAUTION

Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Keep out of reach of children. Read SDS prior to use. For professional use only.



PHYSICAL CHARACTERISTICS

RELATIVE DENSITY	1.28
FLASH POINT	190° F
DRYING TIME	24 hours
TEAR RESISTANCE	27 ppi
PERMEANCE	.57 US perm @ 23 Mil
TENSILE PROPERTIES	
TENSILE STRENGTH	160 PSI
ELONGATION	67%
CLEAN UP	Mineral Spirit or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	Temperatures above 40° F