



PRODUCT CODE: 314

COOL-TOP WHITE RUST INHIBITING & BLEED BLOCKING PRIMER

DESCRIPTION

DEWITT COOL TOP WHITE Rust Inhibiting and Bleed Blocking Primer is a water-based acrylic primer created for use on metal and asphalt roofing systems. It's high-performance formula delivers strong adhesion and critical bleed-blocking properties for asphalt based roofs.

USES

DEWITT'S COOL-TOP WHITE Rust Inhibiting and Bleed Blocking Primer can be used on metal and aluminum substrates.

APPLICATION

Apply when temperatures are above 45°F. Do not apply if rain, heavy dew, or temperatures below 32°F are expected before the product fully dries. Make sure roof is dry before application.

1. Surfaces must be clean and free of dust, dirt, oil, moisture, loose granules, gravel, peeling paint or other foreign matter. Clean with DeWitt's Clean-It or Clean-A-Roof. Rusty metal must be wire brushed of loose rust and primed with a metal rust primer.
2. Must stir before using. Apply by brush, medium nap roller or airless sprayer.

CLEAN-UP: Use mineral spirits or DeWitt's "Remove-It".

COVERAGE

100 sq. ft. per gallon/coat

PACKAGING

5 gallon bucket

CAUTION

Avoid prolonged contact with skin or fumes. If irritation occurs seek medical attention. Keep out of reach of children. Read SDS prior to use. For professional use only.

